PCT

WORLD INTELLECTUAL PROPERTY ORGANIZATION International Bureau



INTERNATIONAL APPLICATION PUBLIS	HED !	UNDER THE PATENT COOPERATION TREATY (PCT)
(51) International Patent Classification 6:		(11) International Publication Number: WO 97/17623
G01S 5/14, H04Q 7/20	A1	(43) International Publication Date: 15 May 1997 (15.05.97)
(21) International Application Number: PCT/AU (22) International Filing Date: 4 November 1996 (ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE).
(30) Priority Data: PN 6374 6 November 1995 (06.11.95	5) A	Published With international search report. With amended claims.
(71) Applicant: BORUNDI INTERNATIONAL PT [AU/AU]; Unit 7, 65-75 Captain Cook Drive, C NSW 2229 (AU).		
(72) Inventors: VUKOVICH, Branko; 3 Kemble Place Plateau, NSW 2107 (US). VEAL, Colin, Preston; 2 Road, Wamboin, NSW 2620 (AU).		
(54) Title: MULTI LAYER VEHICLE TRACKING SYS	TEM	•
(57) Abstract		
to enable the location of the telephone to be determined by	triangond Tim	agement data generated or stored within a GSM digital mobile telephone alation. The management data used includes Base Station Identity Code, ing Advance. The tracking system can also be used to track or locate

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AM	Armenia	GB	United Kingdom	MW	Malawi
AT	Austria	GE	Georgia	MX	Mexico
AU	Australia	GN	Guinea	NB	Niger
BB	Barbados	GR	Greece	NL	Netherlands
BE	Belgium	HU	Hungary	NO	Norway
BF	Burkina Faso	IE	Ireland	NZ	New Zealand
BG	Bulgaria	iT	Italy	PL	Poland
BJ	Benin	IP.	Japan	PT	Portugal
BR	Brazil	KE	Kenya	RO	Romania
BY	Belanus	KG	Kyrgystan	RU	Russian Federation
CA	Canada	KP	Democratic People's Republic	SD	Sudan
CF	Central African Republic		of Korea	SE	Sweden
CG	Congo	KR	Republic of Korea	SG	Singapore
CH	Switzerland	KZ	Kazakhstan	SI	Slovenia
CI	Côte d'Ivoire	u	Liechtenstein	SK	Slovakia
CM	Cameroon	LK	Sri Lanka	SN	Senegal
CN	China	LR	Liberia	SZ	Swaziland
CS	Czechoslovakia	LT	Lithuania	TD	Chad
CZ	Czech Republic	LU	Luxembourg	TG	Togo
DE	Germany	LV	Latvia	TJ	Tajikistan
DK	Denmark	MC	Monaco	TT	Trinidad and Tobago
EE	Estonia	MD	Republic of Moldova	UA	Ukraine
ES	Spain	MG	Madagascar	UG	Uganda
FI	Finland	ML	Mali	US	United States of America
FR	France	MN	Mongolia	UZ	Uzbekistan
GA	Gabon	MR	Mauritania	VN	Viet Nam

10

15

20

25

30

)

MULTI LAYER VEHICLE TRACKING SYSTEM

This invention relates to a method of tracking vehicles and other mobile bodies such as shipping containers, and even people, by using the management data generated within a mobile telephone operating on the GSM digital mobile telephone system.

Several different techniques for tracking of motor vehicles have been implemented in the past. The major disadvantages of these methods are antenna shielding, high infrastructure costs and the need to provide a dedicated communications link from the vehicle to a monitoring station. For example satellite based navigation systems are largely ineffective in high-rise building areas and inside buildings due to antenna shielding, while radio signal triangulation systems require dedicated and expensive infrastructure to be established to provide coverage of the required operating area. Both methods require the addition of a communications capability between the vehicle and the monitoring station. The present invention overcomes these problems by using the very extensive and pre-existing mobile telephone infrastructure, which provides extremely good coverage and a high degree of redundancy so that it is possible to achieve reliable operation in areas where antenna shielding would make the satellite systems unreliable, and whilst not having to fund the infrastructure associated with other radio triangulation systems. The mobile telephone system also provides the required communications link.

The present invention provides a multi-layer tracking system utilising the mobile telephone to provide an initial approximate location (Layer 1), a more precise location by forcing the telephone to gather and report additional information (Layer 2) and, together with other commercial location devices that are controlled via the mobile telephone link, an exact location when required (Layer 3).

The present invention is essentially a radio signal triangulation system the unique features of which are the extraction and use of data that is already generated within the GSM digital mobile telephone to provide the data required to perform the triangulation calculations.

SUBSTITUTE SHEET (Rule 26)

Normal operation of the GSM digital mobile telephone system requires the mobile unit to determine and store a number of items of information relating to the local mobile telephone network. These data are used to make decisions relating to the management of calls to and from that mobile telephone. Some of these data that are of particular relevance to the present invention are:

Base Station Identity Code (BSIC)
Base Station Frequency (ARFCN)
Signal Strength
Signal Quality
Timing Advance (TA)

5

10

15

20

25

30

In normal operation, the mobile telephone will determine and store a full set of these data values in relation to the base station that is best positioned to immediately handle calls on behalf of that mobile. In addition it will determine and store some of these data values for up to six nearby base stations. The data is used internally within the telephone to manage calls to and from the mobile telephone to achieve the most efficient and reliable telephone operation. The present invention takes advantage of the existence of this data within the telephone as well as the ability to control the telephone so as to obtain a more complete set of data. The telephone may then be used to send the data to a remote monitoring station.

Each GSM base station transmits radio signals on one of 124 specific radio frequencies and therefore base stations may be co-located with other base stations or operated separately. When individually sited, the antennassystem is usually (although not necessarily) designed to transmit and receive signals in an omni-directional pattern. When two or more base stations are co-located the antenna system is designed to have directional properties so that each base station services mobile telephones in a sector that is different from the other co-located base stations. Therefore, by determining the Base Station Identity Code it is possible to uniquely identify the operating base station and with knowledge of the antenna characteristics of that base stations

10

15

20

25

30

to determine an approximate azimuth direction from the base station to the, mobile telephone.

In one embodiment of the invention, the above listed management data related to each of the base stations may be used together with information related to the physical location and antenna characteristics of those base stations to determine the position of the mobile telephone by triangulation from the several base stations. The degree of redundancy of the information will provide a sufficiently accurate position definition for many applications.

A second embodiment of the invention provides enhanced accuracy by using the Timing Advance data. This data effectively provides the range from the mobile telephone to the base station. Addition of this information to the triangulation calculation further improves the accuracy of the position fix.

A third embodiment of the invention involves controlling the mobile telephone so as to transfer the call through one or more of the other base stations that are within range. In this way the Timing Advance data for each of the base stations is obtained. Adding this data to the triangulation calculations further enhances the accuracy of the position fix.

In order that the reader may gain a better understanding of the present invention, hereinafter are described one embodiment of the invention, by way of example only. A vehicle is fitted with a security system, a mobile telephone, an interface and control unit (ICU) and a commercial beacon transmitter. In the event of the vehicle being stolen or tampered with, the security system will generate an alarm signal that will trigger the ICU. The ICU may then take control of the mobile telephone and initiate a telephone call to a monitoring station, passing over the link so established the available telephone management data, together with identification details of the vehicle. The ICU will also force the mobile telephone to operate via two or more base stations in order to obtain additional Timing Advance data. At the monitoring station the call may initiate an alarm while at the same time the data received is correlated with known information about each base station in

SUBSTITUTE SHEET (Rule 26)

4

order to perform the triangulation calculations and to present the location information on a map display. The monitoring station operator may then send back control information to the vehicle. This control information could, for example, cause the ICU to activate a commercial beacon transmitter in the vehicle and may also immobilise the vehicle's engine. The monitoring station operator would then despatch an armed guard to the location indicated by the telephone data. The guard would identify the vehicle by means of a radio direction finding system tuned to the tracking transmitter.

SUBSTITUTE SHEET (Rule 26)

12/01/2003, EAST Version: 1.4.1

The claims defining the invention are as follows:

- A vehicle tracking system that uses management data generated within a GSM digital mobile telephone to provide data to enable determination of the position of the mobile telephone by triangulation.
- 5 2. The vehicle tracking system of claim 1 wherein the mobile telephone itself is used as the communications link to pass the acquired data to a monitoring station.
- 3. The vehicle tracking system of claims 1 and 2 wherein the mobile telephone is controlled in such a manner as to force it to operate via two or more base stations so as to generate additional management data in order to refine the triangulation calculations.
 - 4. The vehicle tracking system of any one of claims 1 to 3 wherein the mobile telephone is used to convey control information from a monitoring station to the vehicle in order to control either the tracking system itself or other associated systems within the vehicle so as to enhance the ability of the monitoring station to locate the vehicle.
- 5. The vehicle tracking system of any of claims 1 to 4 applied in a manner so as to provide tracking/location of mobile telephones installed in shipping containers, railway rolling stock or carried on a person.

WO 97/17623

5

10

PCT/AU96/00692

6

AMENDED CLAIMS

[received by the International Bureau on 6 March 1997 (06.03.97); original claims 1-5 replaced by amended claims 1-5 (2 pages)]

- 1. A vehicle tracking system that uses management data stored within a GSM digital mobile telephone to provide information to enable determination of the position of the mobile telephone. In particular, cell identity and Timing Advance (TA) information is accessed directly from the mobile telephone. Cell identity information provides the means of accessing a database containing the location and characteristics of the cell's transmission antenna and thereby a reference point and arc centred on that point, within which the mobile telephone is located. Timing Advance information provides a good estimate of the distance from the base station to the mobile telephone. There is specifically no need for access to, or intervention by or through, a mobile network base station or any other element of the mobile cellular network equipment.
- 15 2. The vehicle tracking system of claim 1 wherein the mobile telephone itself is used as both the source of the location data and the communications link to pass the acquired data to a monitoring station.
- 3. The vehicle tracking system of claims 1 and 2 wherein the mobile telephone is controlled in such a manner as to force it to operate via two or more base stations so as to generate additional management data in order to refine the location calculations. In particular, Timing Advance information is generated for each additional base station so used.
- 4. The vehicle tracking system of any one of claims 1 to 3 wherein the
 mobile telephone is used to convey control information from a
 monitoring station to the vehicle in order to control either the tracking
 system itself or other associated systems within the vehicle so as to
 enhance the ability of the monitoring station to locate the vehicle.

WO 97/17623

PCT/AU96/00692

7

5. The vehicle tracking system of any of claims 1 to 4 applied in a manner so as to provide tracking/location of mobile telephones installed in shipping containers, railway rolling stock or carried on a person.

AMENDED SHEET (ARTICLE 19)

INTERNATIONAL SEARCH REPORT

International Application No.
PCT/AU 96/00692

A.	CLASSIFICATION OF SUBJECT MATTER	t	
Int Cl ⁶ : G0	IS 5/14, H04Q 7/20		
According to	International Patent Classification (IPC) as to be	ab matical attacks of the	
B.	International Patent Classification (IPC) or to be FIELDS SEARCHED	in national classification and IPC	
IPC : G08G	umentation searched (classification system followed by 1/123, 1/127, 1/13; H04B 7, H04Q 7; G01S	3, 5, 13	
Documentation AU : IPC as	a searched other than minimum documentation to the e above	extent that such documents are included in	the fields searched
Electronic data DERWENT: JAPIO:	base consulted during the international search (name	of data base and, where practicable, search	terms used)
C.	DOCUMENTS CONSIDERED TO BE RELEVAN	T	·
Category*	Citation of document, with indication, where a	ppropriate, of the relevant passages	Relevant to claim No.
Р, Х	US 5515419 A (SHEFFER) 7 May 1996 Whole document		1-5
P. X	WO 96/25830 A (EUROPOLITAN AB) 22 Au Abstract	gust 1996	1-5
x	US 5218367 A (SHEFFER) 8 June 1993 Whole document		1-5
x	Further documents are listed in the continuation of Box C	X See patent family annex	
"A" docum not cor "E" earlier interna "L" docum or whic anothe "O" docum exhibit "P" docum	nent defining the general state of the art which is insidered to be of particular relevance document but published on or after the ational filing date ent which may throw doubts on priority claim(s) ch is cited to establish the publication date of a citation or other special reason (as specified) ent referring to an oral disclosure, use, tion or other means	later document published after the in priority date and not in conflict with understand the principle or theory un document of particular relevance; the be considered novel or cannot be consinventive step when the document is document of particular relevance; the be considered to involve an inventive combined with one or more other succombination being obvious to a person document member of the same patent	the application but cited to derlying the invention claimed invention cannot sidered to involve an taken alone claimed invention cannot step when the document is h documents, such a skilled in the art
	al completion of the international search	Date of mailing of the international searce	h report
4 December 19	96	7 JAN 1997	~~
Name and maili AUSTRALIAN PO BOX 200 WODEN ACT AUSTRALIA	ng address of the ISA/AU INDUSTRIAL PROPERTY ORGANISATION 2606 Facsimile No.: (06) 285 3929	Authorized officer S. AGGARWAL	
		Telephone No.: (06) 283 2192	

m PCT/ISA/210 (second sheet) (July 1992) copvak

INTERNATIONAL SEARCH REPORT

International Application No.

C (Continua	PCT/AU 96/00692					
Category*	Citation of document, with indication, where appropriate, of the relevant passag	Relevant to claim No.				
	US 5208756 A (SONG) 4 May 1993					
X	Abstract	1-5				
	US 5389934 A (KASS) 14 February 1995					
A	Whole document	1-5				
	US 5223844 A (MANSELL et. al) 29 June 1993					
A	Whole document	1-5				
		İ				
		·				

Form PCT/ISA/210 (continuation of second sheet) (July 1992) copvak

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No. PCT/AU 96/00692

This Annex lists the known "A" publication level patent family members relating to the patent documents cited in the above-mentioned international search report. The Australian Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

Patent Document Cited in Search Report		Patent Family Member					
US	5515419	EP	643860	wo	9324911	US	5568535
		AU	30712/95	wo	9604155		
wo	9625830	AU	47373/96	SE	9500569	SE	9502976
US	5218367	EP	643860	wo	9324911	US	5515419
		US	5568535	wo	9604155	AU	30712/95
US	5208756	AU	13436/92	WO	9213284		

END OF ANNEX

Form PCT/ISA/210 (extra sheet) (July 1992) copvak